


TECHNICKÝ LIST

C.01

RDSG

Redukcie

S gumeným tesnením



Redukcie koncentrické RDSG
s gumovým tesnením typu

Pozinkovaná oceľ, redukcia s gumovým tesnením

Geometrické rozmery

ØD [mm]	ØD [mm]	l ₁ [mm]	l ₂ [mm]	[kg]
80	150	70	40	0,44
80	180	100	40	0,65
80	200	120	40	0,82
80	250	170	40	1,35
80	315	235	40	2,20
100	250	150	40	1,20
100	315	215	40	2,05
125	315	160	40	1,90
150	315	165	40	1,70
160	355	195	40	1,84
160	400	240	40	3,60
200	355	155	40	1,85
200	400	200	40	3,00
250	400	150	50	2,49
250	450	200	50	3,10
250	500	250	50	5,07
315	355	65	50	2,70
315	400	85	50	1,20
315	450	135	50	2,46
315	500	185	50	3,00
315	560	245	50	4,20
315	630	315	50	4,90
355	400	65	50	2,18
355	450	95	50	1,95
355	500	145	50	3,37
355	560	205	50	3,90
355	630	275	50	5,00
400	450	65	50	1,40
400	500	100	50	2,63
400	560	160	50	3,00
400	630	230	50	6,09
400	710	210	50	7,85
450	500	100	75	1,80
450	560	110	75	3,15
450	630	180	75	5,03
450	710	260	75	7,20
450	800	350	75	13,65
450	900	450	75	15,00
500	560	65	75	2,20
500	600	100	75	3,70
500	630	130	75	4,00
500	710	210	75	6,42
560	630	100	75	4,50
560	710	150	75	4,20
560	800	240	75	16,00
560	900	340	75	8,50
560	1000	440	75	9,00
630	710	380	75	3,29
630	800	170	75	8,80
630	900	270	75	9,00
630	1000	370	75	10,50
710	800	110	75	8,90
710	900	190	75	8,53
710	1000	290	75	10,00
800	900	125	100	7,20
800	1000	200	100	11,00
800	1250	450	100	12,75
900	1000	125	100	8,20
900	1250	350	100	14,00
1000	1250	250	100	13,50